

20000-21
30621 0616
RECYCLING
LOGO 557474

1 DOOR HANDING

HAND OF FURNITURE ACCORDING TO ENGLISH PRACTICE

DOOR OPENING IN

DOOR OPENING OUT

2 POSITIONING OF TEMPLATE

- Align template with cover plate on Lockwood mortice lock.
- Mark and drill necessary holes accurately.
- Remember to mark both sides of door.**
- Do not drill right through door from one side to prevent possible damage to door.**

3 CHANGE OF HANDING

- Verify correct handing of Furniture on the door required. Lever should rotate downwards.
- Position the handle by rotating it 180° to suit the door LH or RH then insert the 4mm stop screw to suit.

4 FOR LOCKS WITH TURN KNOBS

<p>LATCHING OR LOCKING TURNKNOB</p>	<p>EMERGENCY TURNKNOB FUNCTION</p>
--	---

- Mark correct length of connecting bar as shown.
 - For **Latching** or **Locking** turnknob, mark the connecting bar at the edge of the screw on the mounted lock faceplate.
 - For **Emergency** turnknob, mark the connecting bar at the outside edge of the door.
- Cut connecting bar to length, remembering to remove the burr. Attach turn knob to door using screws supplied.
- NOTE: When lockset is in unlocked condition, turn knob to be vertical.**

5 SCREW LENGTH

- If necessary, cut screws to length and deburr ends of screws.
- Ensure Furniture screws do not protrude past the opposite face of the door.**